

# Algae

## Percival® model AL-30L2

Standard SciWhite® LED lighting



### Applications

- Designed for algae that require higher light intensity, short plants that require moderate light intensity and many more applications

### IntellusUltra Controller

The IntellusUltra (C8T) control system adapts to nearly any programming style with a large range of options for optimal control over experiments.

- Robust and reliable, industrial-grade integrated hardware design
- Highly flexible programming capabilities for customized configurations and expansion
- Precise, simultaneous control of up to 7 environmental parameters
- Industry-leading experiment protection and system diagnostics

### IntellusUltra Touchscreen Interface

This high-resolution touchscreen displays advanced settings and data for fine-tuning experiments, including graphs and charts.

- 10.1" IPS, high resolution display with 10-point multi-touch sensitivity
- Tabular and graphical presentation of chamber programs and parameters
- Highly visible process values and alarm notifications
- Enhanced user feedback menus

Please visit [www.percival-scientific.com](http://www.percival-scientific.com) for more information on our control systems.

### SciWhite LED Lighting System

- Two tiers of SciWhite lighting (one on each shelf)
- Programming/real-time control through the IntellusUltra touchscreen
- Intensity up to 440  $\mu\text{moles/m}^2/\text{s}$  of light irradiance measured @ 6" from LEDs
- Dimmable output from 10-100% in one-percent increments

### Airflow/Circulation

- Conditioned air circulates through a rear wall plenum and travels horizontally across each shelf; air then flows vertically upward through the space between the door and shelves back to the unit cooler
- Direction: horizontal
- Airspeed fpm (feet per minute): 50

### AL-30L2 specifications (subject to change without notice)

Temp Range with all lights on	Interior Space volume		Total Shelving Floor Area		Maximum Growing Height		Exterior Dimensions						Light Intensity 6" from lamps unless otherwise noted	Tiers
	°C	ft <sup>3</sup>	m <sup>3</sup>	ft <sup>2</sup>	m <sup>2</sup>	in	cm	width		depth		height		
7-44±0.5	9.9	0.28	6.1	0.6	10.4	26.4	31	78.7	24.4	61.9	46.2	117.3	Up To 440	2

# Algae Percival model AL-30L2

## Cabinet Construction

- Interior constructed of 26-gauge galvanized steel
- Interior floor constructed of 24-gauge polished stainless steel
- Exterior constructed of 24-gauge Galvannealed extra-smooth steel
- NSF-compliant seam design
- Chamber is completely self-contained, suitable for stacking one above the other
- Overall wall thickness is 2" (5.1 cm)
- Highly durable and reflective white coating

## Insulation

- Woodless construction using 2" non-CFC Urethane insulation with closed cell-structure density of 2.2 lbs/ft<sup>3</sup>

## Door

- One door opening 26.7" x 29.8" (67.8 cm x 75.6 cm) provides full access to the chamber interior
- Magnetic gasket provides a tight seal to door frame

## Interior Space

- 9.9 ft<sup>3</sup> (0.28 m<sup>3</sup>) with work area of 6.1 ft<sup>2</sup> (0.6 m<sup>2</sup>) provided on two tiers

## Shelving

- Two tiers of white epoxy coated steel wire shelving (each shelf is 16.5"D x 26.5"W [41.9 cm x 67.3 cm])
- Growing height is 10.4" (26.4 cm) with shelves evenly spaced

## Refrigeration

- Self-contained air-cooled condensing unit with hot gas bypass system (continuous running condensing unit ensures precise temperature control by alternately cycling refrigerant and hot gas to coil; this also prolongs life of compressor and eliminates risk of ice buildup in coil)
- Extended stem solenoid valves for quiet and long life operation
- Rear chamber wall-mounted evaporator coil incorporates an air circulation fan
- Heat rejection to ambient (standard chamber) = 2,054 BTU/hr

## Temperature Range

- 7°-44°C (±0.5°C) lights on; 2°-44°C (±0.5°C) lights off

## Humidity Control (optional)

- Ultrasonic humidifier with advanced RH sensor (H11)
- Ultrasonic humidifier and dehumidifier with advanced RH sensor (H12)
- Ultrasonic humidifier with electronic RH sensor (H14)
- Ultrasonic humidifier and dehumidifier with electronic RH sensor (H15)

*See other specification sheets or contact Percival Scientific for additional information.*

## Options (most popular)

- IntellusUltra Connect (C9)
- Additive CO<sub>2</sub> control
- CO<sub>2</sub> removal system
- Self-contained water-cooled condensing unit
- Dry alarm contacts
- Closed loop dimmable lighting with PAR light sensor (Q22)
- Open loop dimmable lighting per tier (Q23<sup>+</sup>)
- Extended temperature ranges available
- Convenience receptacles

*Contact [info@percival-scientific.com](mailto:info@percival-scientific.com) for additional information.*

## Electrical Service Requirements

- 115/1/60 with NEMA 5-15P plug provided (with standard chamber)
- RLA=9.9, MCA=12.4

## Regulatory Standards

- Electrical Safety: UL-508A, certified and labelled by Percival Scientific under UL file number E340161
- Quality System: ISO 9001:2015, certified under DQS, Inc. under certification number 10017261

## Helping You Create Better Science

Percival Scientific controlled environment systems are the culmination of over 60 years of design and manufacturing experience. We developed our high-quality products through direct partnerships within the scientific community. Our controlled environments are known for their customizable designs and superior, long-lasting performance. Creativity, passion, technical expertise and attention to detail drive our scientific innovation, and we are proud to help you create better science.



Percival Scientific, Inc.

505 Research Drive • Perry, IA 50220 USA

800.695.2743 • 515.465.9363 • Fax: 515.465.9464

[www.percival-scientific.com](http://www.percival-scientific.com)